

AIR LIQUIDE

Pressure Regulators, Bottle Pressure Regulators, Relief Valves Stainless Steel SS 316L - Brass

Pressure Regulators



DLM 240-15-50

P/N AL423321

Brass

Single stage

Inlet pressure: max. 240 bar

Outlet control range: 0.5 up to 15 bar

Flow capacity: 50 Nm³/h (N₂)

Operating temperature: -20°C up to +50°C

DLM 240-50-100

P/N AL423308

Brass

Single stage

Inlet pressure: max. 240 bar

Outlet control range: 5 up to 50 bar

Flow capacity: 100 Nm³/h (N₂)

Operating temperature: -20°C up to +50°C



DIM 240-3-5

P/N AL422501

SS 316 L

Single stage

Inlet pressure: max. 240 bar

Outlet control range: 0.3 up to 3 bar

Flow capacity: 5 Nm³/h (N₂)

Operating temperature: -20°C up to +50°C

DIM 240-30-30

P/N AL415995

SS 316 L

Single stage

Inlet pressure: max. 240 bar

Outlet control range: 5 up to 30 bar

Flow capacity: 30 Nm³/h (N₂)

Operating temperature: -20°C up to +50°C



BSI 50-1-2

P/N AL423103

SS 316 L

Single stage

Inlet pressure: max. 50 bar

Outlet control range: 0.05 up to 1 bar

Flow capacity: 2 Nm³/h (N₂)

Operating temperature: -20°C up to +50°C

Bottle Pressure Regulators



HBD 240-10-12

P/N AL422163

Brass

Dual stage

Inlet pressure: max. 240 bar

Outlet control range: 0.1 up to 7 bar

Flow capacity: 9.4 Nm³/h (N₂)

Operating temperature: -40°C up to +74°C



HBD 240-10-12-S

P/N AL422164

SS 316 L

Dual stage

Inlet pressure: max. 240 bar

Outlet control range: 0.1 up to 7 bar

Flow capacity: 9.4 Nm³/h (N₂)

Operating temperature: -40°C up to +74°C

Relief Valves



SV 805 ES - SS 316 L

P/N AL421145

SV 805 MS - brass

P/N AI421144

Connections

Inlet: G3/8

Outlet: for tube ø6mm

Outlet pressure to atmosphere 16 bar (others on request)